

Mastervolt:	50902005 50Hz	50902055 60Hz	50902006 50Hz ungrounded	50902056 60Hz ungrounded	50902020 50Hz mobile
Voltage:	230V	120V	230V	120V	230V
Power:	5KW	5KW	5KW	5KW	5KW
Speed:	3000 RPM	3600 RPM	3000 RPM	3600 RPM	3000 RPM
Engine:	L2E	L2E	L2E	L2E	L2E
# of cylinders:	2	2	2	2	2
Cylinder capacity:	635cc	635cc	635cc	635cc	635cc
fuel consumption:	1.2 - 5l/u 0.26 – 0.66 gph	1.2 - 5l/u 0.26 – 0.66 gph	1.2 - 5l/u 0.26 – 0.66 gph	1.2 - 5l/u 0.26 – 0.66 gph	1.2 - 5l/u 0.26 – 0.66 gph
pump capacity:	18l/m 4.8 gpm	18l/m 4.8 gpm	18l/m 4.8 gpm	18l/m 4.8 gpm	18l/m 4.8 gpm
Engine cooling:	Water Cooled (Indirectly)	Water Cooled (Indirectly)	Water Cooled (Indirectly)	Water Cooled (Indirectly)	Water Cooled (Indirectly)
Connection outlet:	40mm 15/8"	40mm 15/8"	40mm 15/8"	40mm 15/8"	40mm 15/8"
Start battery: (optional)	12V70Ah	12V70Ah	12V70Ah	12V70Ah	12V70Ah
Dimensions: (hxwxh):	660x495x550 mm 26x19.5x21.7inch	660x495x550 mm 26x19.5x21.7inch	660x495x550 mm 26x19.5x21.7inch	660x495x550 mm 26x19.5x21.7inch	660x495x550 mm 26x19.5x21.7inch
Weight:	178kg 392 lbs	178kg 392 lbs	178kg 392 lbs	178kg 392 lbs	178kg 392 lbs